

# EASY

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>EASY</b>
FORMATI-SIZES :	<b>45X45</b>
NOMI-NAMES :	<b>EASY BROWN - EASY SAND - EASY CREAM - EASY GREY - EASY PEARL</b>
COLORI-COLOURS :	<b>MARRONE - BEIGE - SABBIA - GRIGIO (chiaro-scuro)</b> <b>BROWN - BEIGE - SAND - GREY (light-dark)</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS :	<b>5</b>

## ACCESSORI - ACCESSORIES

FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	<b>X</b>
DECORI-DECORS :		GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno  
*Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile*

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B I a** - Class of **B I a**

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		<b>6</b>	UNI EN 101
RESISTENZA ALL'ABRASIONE DELLA SUPERFICIE- PEI <i>RESISTANCE TO SURFACE ABRASION-PEI</i>		<b>IV</b>	EN ISO 10545-7
SPESSORE <i>THICKNESS</i>		<b>9,5 mm</b>	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		<b>R9</b>	DIN 51130
		<b>&gt; μ 0,4</b> Attrito soddisfacente - Satisfactory Friction	D.M. 236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		<b>3</b>	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		<b>GA-GLA-GHA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE <i>BENDING STRENGTH</i>		<b>&gt; 35 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		<b>≤ 0,2%</b>	EN ISO 10545-3