

BYBLOS

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	BYBLOS
FORMATI-SIZES :	60x60 - 45x45 - 30x60
NOMI-NAMES :	BY BLACK - BY SMOKE - BY SAND - BY BRONZE - BY GREY
COLORI-COLOURS :	NERO - ANTRACITE - BEIGE - BRONZO - GRIGIO BLACK - ANTHRACITE - BEIGE - BRONZE - GREY
SUPERFICIE-SURFACE :	SEMILUCIDA - SEMI-MAT
NR. COLORI-NR. COLOURS:	5

ACCESSORI - ACCESSORIES









FONDI-TILES :	X	BATTISCOPIA-BULLNOSE:	X
DECORI-DECORS:	X	GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B I a** - Annex G - Group **B I a**

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		7	UNI EN 101
RESISTENZA ALL'ABRASIONE DELLA SUPERFICIE- PEI <i>RESISTANCE TO SURFACE ABRASION-PEI</i>		IV	EN ISO 10545-7
SPESSORE <i>THICKNESS</i>		9,5 - 10 mm	EN ISO 10545-2
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		3	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		GA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE <i>BENDING STRENGTH</i>		≥ 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		≤ 0,4%	EN ISO 10545-3