

# MDF Panelling with fixed tongue

Technical data sheet · Issue: 01-2010

<b>Product specifications</b> Length of panelling Profile width Cover width Thickness of panelling Content of package Packaging		2600 mm 190 mm 185 mm 8 mm 7 pcs. (= 3,458 m <sup>2</sup> ) Shrinking foil
<b>Tolerances</b> Dimension tolerance  Density of MDF core board Swelling of MDF core board	<b>Requirements</b> (EN 68740) length width thickness	+/- 2,0 mm +/- 1,0 mm +/- 0,5 mm ≥ 700 kg / m <sup>3</sup> ≥ 20 % (Suitable for damp rooms)
<b>Surfaces</b> Finish foils	<b>Requirements</b> Light resistance according to DIN 438.2 Temperatur resistance	Factor 6  65°C
<b>Physical attributes</b> Reaction to fire  Fields of application Fixation	<b>Requirements</b> (EN 13501-1)	Dfl-s1 / B2 Normal flammable All dry and heated interior rooms Standard installation: Clip No. 2 / On (planed wooden) battons Installation in damp rooms (kitchens, bathrooms): On (planed wooden) counter battons



BHK Holz- u. Kunststoff KG · H. Kottmann · Heidfeld 5 · D-33142 Büren

Telefon: +49 (0) 29 51-60 04-0 · Telefax: +49 (0) 29 51-54 99 · Internet: [www.bhk.de](http://www.bhk.de) · E-Mail: [info@bhk.de](mailto:info@bhk.de)