

# N.Y.C.

# Polis

CERAMICHE

DATA - DATE: 27 MAR. 2010

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

**DATI GENERALI - GENERAL DATA**

SERIE-SERIES :	<b>N.Y.C.</b>
FORMATI-SIZES :	<b>20X45</b>
NOMI-NAMES :	<b>NOLITA - TRIBECA - SOHO - BOCOCO - MIDTOWN - BROADWAY</b>
COLORI-COLOURS :	<b>NERO - ANTRACITE - GRIGIO - BIANCO - TABACCO - BEIGE</b> <b>BLACK - ANTHRACITE - GREY - WHITE- TOBACCO - BEIGE</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS :	<b>6</b>

**ACCESSORI - ACCESSORIES**






FONDI-TILES :	<b>X</b>	BATTISCOPA-BULLNOSE:	
DECORI-DECORS:	<b>X</b>	GRADINO-STEP:	

USO PREVALENTE - USAGE: Riv. Interno  
Indoor Wall Tile

**CARATTERISTICHE TECNICHE - TECHNICAL DATA**

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza B III - Annex G - Group B III

RESISTENZA AL GELO FROST RESISTANCE		<b>Non richiesta</b> Not required	EN ISO 10545-12
SPESSORE THICKNESS		<b>9,2 mm</b>	EN ISO 10545-2
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		<b>GA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE BENDING STRENGTH		<b>20 N/mm<sup>2</sup></b>	EN ISO 10545-4
RESISTENZA AL CAVILLO CRAZING RESISTANCE		<b>SI</b>	EN ISO 10545-11