

EVOLUTION

Polis
CERAMICHE
DATA - DATE: 01 OTT. 2012

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	EVOLUTION
FORMATI-SIZES :	60X60 - 30X60 - 30X30
NOMI-NAMES :	NIGHT - SUEDE - BRICK - CLAY - MILK
COLORI-COLOURS :	ANTRACITE - TORTORA - COTTO - BEIGE - BIANCO/BEIGE ANTHRACITE - DOVE - COTTO - BEIGE - WHITE / BEIGE
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS :	5

ACCESSORI - ACCESSORIES










FONDI-TILES :	X	BATTISCOPA-BULLNOSE:	X
DECORI-DECORS:	X	GRADINO-STEP:	X

USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno
Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B I a** - Class of **B I a**

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		8	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm³	EN ISO 10545-6
SPESSORE THICKNESS		9,5 - 10 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R9	DIN 51130
		> μ 0,4 Attrito soddisfacente - Satisfactory Friction	D.M. 236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		3	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		UA-ULA-UHA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE BENDING STRENGTH		> 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		0,20%	EN ISO 10545-3