

# N.Y.C.

**Polis**  
CERAMICHE  
DATA - DATE: 13 GEN. 2014

SCHEMA TECNICA PRODOTTO - TECHNICAL DATA SHEET

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>N.Y.C.</b>
FORMATI-SIZES :	<b>15X60 - 30X60 - 60X60 - 45X45 - 45x90 - 90x90</b>
NOMI-NAMES:	<b>NOLITA - TRIBECA - SOHO - BOCOCO - MIDTOWN - BROADWAY</b>
COLORI-COLOURS :	<b>NERO - ANTRACITE - GRIGIO - BIANCO - TABACCO - BEIGE</b> <b>BLACK - ANTHRACITE - GREY - WHITE- TOBACCO - BEIGE</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS:	<b>6</b>










## ACCESSORI - ACCESSORIES

FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	<b>X</b>
DECORI-DECORS:	<b>X</b>	GRADINO-STEP:	<b>X</b>

USO PREVALENTE - USAGE: Pav. Interno - Riv. Esterno - Riv. Interno  
*Indoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile*

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)  
Appendice G - Classe di appartenenza B I a - Annex G - Group B I a

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		<b>7</b>	UNI EN 101
RESISTENZA ALL'ABRASIONE <i>RESISTANCE TO DEEP ABRASION</i>		<b>≤ 175 mm<sup>3</sup></b>	EN ISO 10545-6
SPESSORE <i>THICKNESS</i>		<b>9,5 - 11 mm</b>	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		<b>R9</b>	DIN 51130
		<b>&gt; μ 0,4</b> Attrito soddisfacente - Satisfactory Friction	D.M. 236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		<b>5</b>	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		<b>UA-ULA-UHA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE <i>BENDING STRENGTH</i>		<b>&gt; 35 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		<b>≤ 0,5%</b>	EN ISO 10545-3

