

DOWNTOWN 45x90 - 60x120

Polis
CERAMICHE
DATA - DATE: 07 lug 14

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres porcellanato colorato in massa - Fully-coloured porcelain tiles

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	DOWNTOWN
FORMATI-SIZES :	30x60 - 45x90 - 60x120
NOMI-NAMES:	DIAGONAL - MITTE - TORTORA
COLORI-COLOURS :	BEIGE - GRIGIO - TORTORA BEIGE- GREY - TAUPE
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS:	3

ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPIA-BULLNOSE:	X
DECORI-DECORS:	X	GRADINO-STEP:	X



USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno

Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B1a** - Annex G - Group **B1a**

RESISTENZA AL GELO FROST RESISTANCE		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) HARDNESS (MOHS)		7	UNI EN 101
RESISTENZA ALL'ABRASIONE RESISTANCE TO DEEP ABRASION		≤ 175 mm³	EN ISO 10545-6
SPESSORE THICKNESS		9,5 - 11 mm	EN ISO 10545-2
SCIVOLOSITA' SLIPPERINESS		R 9	DIN 51130
		A+B (A+B+C)	DIN 51097
		>μ 0,40 Attrito soddisfacente - Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE RESISTANCE TO STAINING		5	EN ISO 10545-14
RESISTENZA CHIMICA RESISTANCE TO CHEMICALS		UA-ULA-UHA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE BENDING STRENGTH		> 35 N/mm²	EN ISO 10545-4
ASSORBIMENTO WATER ABSORPTION		≤ 0,5%	EN ISO 10545-3