

# N.Y.C. 2.0

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

## DATI GENERALI - GENERAL DATA

SERIE-SERIES :	<b>N.Y.C. 2.0</b>
FORMATI-SIZES :	<b>60X60</b>
NOMI-NAMES :	<b>NOLITA - TRIBECA - SOHO - MIDTOWN</b>
COLORI-COLOURS :	<b>NERO - ANTRACITE - GRIGIO - TABACCO</b> <b>BLACK - ANTHRACITE - GREY - TOBACCO</b>
SUPERFICIE-SURFACE :	<b>MAT</b>
NR. COLORI-NR. COLOURS :	<b>4</b>

## ACCESSORI - ACCESSORIES

FONDI-TILES :	<b>X</b>	BATTISCOPIA-BULLNOSE:	
DECORI-DECORS :		GRADINO-STEP:	

USO PREVALENTE - USAGE: Pav. Esterno  
*Outdoor Floor Tile*

## CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)  
Appendice G - Classe di appartenenza B I a - Annex G - Group B I a

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		<b>SI</b>	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		<b>7</b>	UNI EN 101
RESISTENZA ALL'ABRASIONE <i>RESISTANCE TO DEEP ABRASION</i>		<b>≤ 175 mm<sup>3</sup></b>	EN ISO 10545-6
SPESSORE <i>THICKNESS</i>		<b>20 mm</b>	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		<b>R11</b>	DIN 51130
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		<b>3</b>	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		<b>UA-U LA-UHA</b>	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE <i>BENDING STRENGTH</i>		<b>&gt; 35 N/mm<sup>2</sup></b>	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		<b>≤ 0,5%</b>	EN ISO 10545-3