

ECO STONES MATTE 25X25

ONIX[®]









TABLA DE MEDIDAS Y PESOS

WEIGHT AND DIMENSIONS - TABLEAU DES
POIDS ET DIMENSIONS - GRÖÖBE UND GEWICHTE

FORMATO SIZE FORMAT FORMAT	25x25mm 1" x 1"
ESPESOR THICKNESS EPAISSEUR STÄRKE	~ 4,9mm 0.19"
MEDIDAS HOJAS SHEETS SIZE DIMENSION PLAQUES ABMESSUNG DER BLÄTTER	311x311mm 12.24"x12.24"
JUNTA JOINT JOINT ABMESSUNG DER FUGE	~ 1,5mm 0.02"
PESO WEIGHT POIDS GEWICHT	0,91 kg 2.01 lb
CANTIDAD POR CAJA QUANTITY PER BOX QUANTITE PER CARTON QUANTITÄT PRO KARTON	0,49 m ² 5.27 sqft
CAJAS POR PALLET CARTONS PER PALLET CARTONS PER PALETTE KARTONS PRO PALETTE	216
PESO PALET PALLET WEIGHT POIDS PALETTE PALETTENGEWICHT	987,12 kg 2,175.6 lb

CARACTERÍSTICAS TÉCNICAS

TEST DATA - CARACTÉRISTIQUES TECHNIQUES -
TECHNISCHE EIGENSCHAFTEN

UNE EN ISO 10545 (13)	
RESISTENCIA A LOS AGENTES QUÍMICOS RESISTANCE TO CHEMICAL AGENTS RESISTANCE AUX PRODUITS CHIMIQUES SÄURE - UND LAUGHENBESTÄNDIGKEIT	resistente resistant résistant beständig
UNE EN ISO 10545 (9)	
RESISTENCIA A LOS CAMBIOS DE TEMPERATURA RESISTANCE TO THERMAL SHOCKS RESISTANCE AUX CHOCS THERMIQUES TEMPERATURWECHSELBESTÄNDIGKEIT	resistente resistant résistant beständig
UNE EN ISO 10545 (3)	
ABSORCIÓN DE AGUA WATER ABSORTION ABSORPTION D'EAU WASSERAUFNAHME	nula none nulle null
DIN 51094	
RESISTENCIA DE LOS COLORES A LA LUZ COLOURS RESISTANCE TO FADING RESISTANCE DES COULEURS A LA LUMIERE FARBBESTÄNDIGKEIT	resistente resistant résistant beständig
UNE EN ISO 10545 (12)	
RESISTENCIA AL HIELO FROST RESISTANT RESISTANCE AU GEL FROSTBESTÄNDIGKEIT	resistente resistent résistent beständig
DIN 51130:2004	
RESISTENCIA AL DESLIZAMIENTO CON CALZADO SLIP RESISTANCE WEARING SHOES RESISTANCE AU GLISSEMENT PIEDS CHAUSSEES RUTSCHFESTIGKEIT MIT SCHUHEN	R11 R11 R11
DIN 51097	
RESISTENCIA AL DESLIZAMIENTO SIN CALZADO SLIP RESISTANCE IN BARE SHOES RESISTANCE AU GLISSEMENT PIEDS NUS RUTSCHFESTIGKEIT OHNE SCHUHEN	Clase C Class C Classe C Klasse C
UNE-EN-ISO-10545-14	
RESISTENCIA A LAS MANCHAS RESISTANCE TO STAINING RÉSISTANCE AUX TACHES FLECKENBESTÄNDIG	Clase 5 Class 5 Classe 5 Klasse 5

TEST ASTM

TEST PERFORMED AND REQUIREMENTS	CONCLUSIONS
Range of Thickness (ASTM C499)	passes
Facial Dimensions (ASTM C499)	passes
Wedging (ASTM C502)	passes
Water Absorption (ASTM C373)	passes
Thermal Shocks (ASTM C484)	passes
Bond Strenght (ASTM C482)	passes
Crazing (ASTM C424)	passes