

2.0 MERHABA

SCHEDA TECNICA PRODOTTO - TECHNICAL DATA SHEET

Gres porcellanato colorato in massa - Fully-coloured porcelain tiles

DATI GENERALI - GENERAL DATA

SERIE-SERIES :	MERHABA
FORMATI-SIZES :	60x60 - 45x90 - 90x90
NOMI-NAMES :	MERHABA BEIGE
COLORI-COLOURS :	BEIGE BEIGE
SUPERFICIE-SURFACE :	MAT
NR. COLORI-NR. COLOURS :	1

ACCESSORI - ACCESSORIES

FONDI-TILES :	X	BATTISCOPA-BULLNOSE:	
DECORI-DECORS:		GRADINO-STEP:	X










USO PREVALENTE - USAGE: Pav. Interno - Pav. Esterno - Riv. Esterno - Riv. Interno

Indoor Floor Tile - Outdoor Floor Tile - Outdoor Wall Tile - Indoor Wall Tile

CARATTERISTICHE TECNICHE - TECHNICAL DATA

Conforme alla norma EN 14411 (ISO 13006) - Compliant with standards EN 14411 (ISO 13006)

Appendice G - Classe di appartenenza **B I a** - Class of **B I a**

RESISTENZA AL GELO <i>FROST RESISTANCE</i>		SI	EN ISO 10545-12
DUREZZA SUPERFICIE (MOHS) <i>HARDNESS (MOHS)</i>		8	UNI EN 101
RESISTENZA ALL'ABRASIONE <i>RESISTANCE TO DEEP ABRASION</i>		≤ 175 mm₃	EN ISO 10545-6
SPESSORE IN BASE AL FORMATO <i>THICKNESS IN REFERENCE TO THE SIZES</i>		20 mm	EN ISO 10545-2
SCIVOLOSITA' <i>SLIPPERINESS</i>		R 11	DIN 51130
		C (A+B+C) >μ 0,40	DIN 51097
		Attrito soddisfacente Acceptable Friction	D.M.236-89 Rif. B.C.R.A.
RESISTENZA ALLE MACCHIE <i>RESISTANCE TO STAINING</i>		5	EN ISO 10545-14
RESISTENZA CHIMICA <i>RESISTANCE TO CHEMICALS</i>		UA-ULA-UHA	EN ISO 10545-13
RESISTENZA ALLA FLESSIONE/MODULO DI ROTTURA <i>BENDING STRENGTH/BREAKING STRENGTH</i>		≥ 45 N/mm²	EN ISO 10545-4
ASSORBIMENTO <i>WATER ABSORPTION</i>		≤ 0,2%	EN ISO 10545-3